

2022 Hot Shot Rules

DISCLAIMER:

The rules and or regulations set forth herein are designed to provide for the orderly conduct of racing events, to establish minimum acceptable requirements for such events. These rules shall govern the condition of all events, and by participating in these events. No express or implied warranty of safety shall result from publication of or compliance with these rules or regulations. They are intended as a guide for the conduct of the sport and are in no way a guarantee against injury or death to a participant, spectator, or official. The word "track" refers to Talladega Short Track.

CARS:

1. 96" minimum wheelbase.
2. 102" maximum wheelbase.
3. Rear wheel drive OK. NO GM rear wheel drives.
4. No low-profile cars such as Camaro, Firebird, or Mustang.
5. Front and Rear tow loop REQUIRED.
6. Rear-end must be stock for make and model.
7. NO Locked Rear-Ends.
8. WEIGHT – ALL Cars must weigh 2,200 lbs. Minimum – NO Burn off!
9. Any weight/lead MUST be mounted with two(2) 1/2" bolts or larger, and painted white with car # on it.

SUSPENSION AND FRAME:

1. No altering in any way.
2. Stock shocks in stock position.
3. No adjustable or aluminum shocks.

BODY:

1. 2 door or 4 doors allowed.
2. All glass must be removed. Windshield may remain if desired.
3. May remove back seat, but opening needs to be covered in metal.
4. Doors MUST be welded shut.
5. Dash must remain intact.
6. NO Cutting of body anywhere.
7. All body panels must be on car. Gutting is allowed, but car should remain reasonable appearance of stock car.
8. Driver's door may be hulled out for roll cage.
9. Four-point cage may be used. 1 3/4" diameter steel pipe minimum.
10. 4" rollover bar may be used. If using 4" rollover bar, an 18" wide 3/8" thickness steel plate must be welded or bolted to outside of driver's door. Plate must extend 18" to the front and 18" to the rear of door seams.

ADD-ONS:

1. Seat belt and harness required. Seat belts must be minimum 3" wide.
2. Racing seats allowed or factory stock seat OK.
3. Steering wheel center must be padded.
4. Fuel cell may be used. If fuel cell is used, it must be mounted inside a 0.20-gauge metal box secured by minimum 1" steel straps.
5. Driver's must have an approved full fire suit (top and bottom). SFI-approved suit recommended, not required.
6. Snell rated SA2010, SA2015, or SA2020 full-face helmet required.
7. Recommended that driver's use head and neck restraint system.
8. ALL cars REQUIRED to have fire extinguisher in car, and within reach of the driver.

WHEELS:

1. Steel wheels only.
2. Maximum 7-inch width wheel, 1" tolerance. May be double centered.
3. Oversized lug nuts required on all 4 wheels.
4. Steel racing wheels only on right front and right rear.

TIRES:

1. Maximum size P235/70 R15 highway DOT tires only.

2. No racing tires. IMCA G60 tires OK as option.
3. All 4 tires must be same size (example: 15,14, or 13 inch all the way around).

BRAKES:

1. Must remain stock for make and model of car.
2. No adjusters.

***Track reserves the right to make the driver who wins feature invert the following race. Number of cars to be inverted will be announced. ***

This does not apply to special events or championship races