



## 2022 STREET STOCK DIMENSIONS

- A)** Tail of car must be completely enclosed. NO holes in tail pieces. Stock plastic, sheet metal or aluminum tail pieces allowed and must extend quarter panel to quarter panel with no gaps. Also, tailpiece must be mounted straight up and down (no angle) and extend below frame horns in a straight, horizontal line from quarter panel to quarter panel.
- B)** Body must be minimum height of 5" off the ground at all points around car.
- C)** Maximum distance of 45" from furthest point on front of nose to front cross member (Measured from where lower control arm bolt goes through cross-member to farthest point of nose).
- D)** Rear Quarter Panels - 48" maximum measured from center of axle straight line to rear of car.
- E)** Rear Quarter Panels - 51" maximum measured from center of axle to top of quarter panel/bottom of spoiler.
- F)** Body must not be any wider (from side to side) than 68", measured at driver's compartment.
- G)** Maximum 66" width from side to side measured at front of door.
- H)** Gradual nose rake - 3" maximum.
- I)** 60" maximum width of rear spoiler.
- J)** 13" minimum window opening.
- K)** 40" maximum Deck Height. Deck height must be measured from bottom of spoiler to the ground.
- L)** Rear of car must not exceed 64" wide, measured at top of rear deck.

